

# Refrigerant-Grade Hydrocarbons

Dynatemp is your one-stop-shop for all your refrigerant needs

## R-290 Propane



14oz (400g) net weight per cylinder

12 cans and one piercing valve (p/n PV-14) per case

DOT Certification DOT-2Q

R-290 (Propane), part number R290/14, applications include household refrigerators, freezers, or combination refrigerators and freezers, in vending machines, and in-room air conditioning units.



## New Service Tools Available!

**\$9.00 (NEW!)** 1/4" Piercing Valve Liquid Charging Base Part # PV-14XL  
**\$7.00** Standard 1/4" Piercing Valve Part # PV-14  
**\$10.85** 1/4" Service Hose with Ball Valve Part # HCSH-12-14-14



## R-600a Isobutane



14oz (400g) net weight per cylinder

12 cans and one piercing valve (p/n PV-14) per case

DOT Certification DOT-2Q

R600a (Isobutane), part number R600A/14, applications include retail food refrigeration (stand-alone commercial refrigerators and freezers) and in vending machines.

**NEW** extra-large PV-14XL valve supports the cylinder for **HANDS-FREE CHARGING** of Hydrocarbons into a system.

## FluorFusion Specialty Chemicals™ Hydrocarbons

- FluorFusion Specialty Chemicals™ provides the highest quality hydrocarbons and refrigerants. We're your one-stop-shop for all your refrigerant needs.
- Isobutane (R-600a) and propane (R-290) are EPA SNAP approved for household refrigerators, freezers, and combination refrigerators and freezers
- Meets or exceeds AHRI-700 specifications
- **Free shipping** when combined with other refrigerant purchases
- **WARNING:** For professional use only! R290 and R600a are highly flammable refrigerants and should only be used in equipment in which it is specified.

For more information visit [dynatempintl.com/dynaproduct](http://dynatempintl.com/dynaproduct) or call 717-713-2772

